

Electric powered forklift 4.0 - 5.0 ton

TRIGO⁸⁰



Electric powered forklift 4.0 - 5.0 ton

Truck specifications						8FBMT40	8FBMT45	8FBMT50
Identification	1.1	Manufacturer				Toyota	Toyota	Toyota
	1.2	Model				8FBMT40	8FBMT45	8FBMT50
	1.3	Drive				Electric	Electric	Electric
	1.4	Operator type				Rider seated	Rider seated	Rider seated
	1.5	Load capacity/rated load	Q	kg		4000	4500	4990
	1.6	Load centre	c	mm		500	500	600
	1.8	Load distance, centre of drive axle to fork	x	mm		518	518	528
	1.9	Wheelbase	y	mm		2030	2030	2030
Weight	2.1	Service weight		kg		6556	7086	7721
	2.2	Axle load, with load, front/rear		kg		9555 / 1102	10261 / 1325	11316 / 1406
	2.3	Axle load, without load, front/rear		kg		3558 / 3099	3515 / 3572	3548 / 4173
Tyres	3.1	Tyre: C = Cushion, SE = Super elastic, PN = Pneumatic, TW = Twin				SE	SE	SE
	3.2	Tyre size, front				250-15	250-15	28x12,5-15
	3.3	Tyre size, rear				23x9-10	23x9-10	23x9-10
	3.5	Wheels, number front/rear (x = driven wheels)				2 / 2	2 / 2	2 / 2
	3.6	Track width, front	b ₁₀	mm		1119	1119	1145
	3.7	Track width, rear	b ₁₁	mm		1113	1113	1113
	3.8	Track width, wheel	b ₁₂	mm		1113	1113	1113
Dimensions	4.1	Tilt of mast/fork carriage forward/backward	α/β	deg		5/10	5/10	5/10
	4.2	Height, mast lowered	h ₁	mm		2500	2500	2500
	4.3	Free lift	h ₂	mm		130	130	140
	4.4	Lift	h ₃	mm		3300	3300	3300
	4.5	Lift height	h ₂₃	mm		3350	3350	3360
	4.5	Height, mast extended	h ₄	mm		4156	4156	4156
	4.7	Height of overhead guard (cab)	h ₆	mm		2360	2360	2360
	4.8	Seat height/stand height	h ₇	mm		1277	1277	1277
	4.12	Coupling height	h ₁₀	mm		550	550	550
	4.19	Overall length	l ₁	mm		3907	3947	4272
	4.20	Length to face of forks	l ₂	mm		2907	2947	3072
	4.21	Overall width	b ₁	mm		1345	1345	1440
	4.22	Fork dimensions	s/e/l	mm		50/150/1000	50/150/1000	60/150/1200
	4.23	Fork carriage DIN 15 173, class/type A, B				IIIA	IIIA	IIIA
	4.24	Fork-carriage width	b ₃	mm		1170	1170	1170
	4.31	Ground clearance, with load, below mast	m ₁	mm		150	150	150
	4.32	Ground clearance, centre of wheelbase	m ₂	mm		152	152	152
	4.33	Aisle width for pallets 1000x1200 crossways	A _{st}	mm		4260	4276	4412
	4.34	Aisle width for pallets 800x1200 lengthways	A _{st}	mm		4460	4476	4612
	4.35	Turning radius	W _a	mm		2543	2558	2686
	4.36	Internal turning radius	b ₁₃	mm		685	685	685
Performance data	5.1	Travel speed, with/without load		km/h		18/18	18/18	18/18
	5.2	Lift speed, with/without load		m/s		0,35/0,46	0,35/0,46	0,33/0,46
	5.3	Lowering speed, with/without load		m/s		0,55/0,46	0,55/0,46	0,55/0,46
	5.5	Drawbar pull, with/without load		N		12420	12420	12420
	5.6	Max. drawbar pull, with/without load		N		22000	22000	22000
	5.7	Gradeability, with/without load		%		11,3/17	9,5/16,8	8,8/15,8
	5.8	Max. gradeability, with/without load		%		15/25	14/24	13/23
	5.9	Acceleration time, with/without load		s		5,1/4,5	5,2/4,5	5,3/4,6
	5.10	Service brake				Mechanical/hydraulic	Mechanical/hydraulic	Mechanical/hydraulic
	5.11	Service brake				Mechanical/hydraulic	Mechanical/hydraulic	Mechanical/hydraulic
Electric motor	6.1	Drive motor rating S2 60 min		kW		25,2	25,2	25,2
	6.2	Lift motor rating S3 15%		kW		25,5	25,5	25,5
	6.3	Battery acc. to DIN 43 531/35/36 A, B, C, no				43536	43536	43536
	6.4	Battery voltage, nominal capacity K _s		V/Ah		80 / 840	80 / 840	80 / 840
	6.5	Battery weight		kg		2178	2178	2178
	6.6	Energy consumption acc. to EN16796:2016		kWh/h		9.8	10.8	12.2
Other	8.1	Type of drive control				AC	AC	AC
	8.2	Operating pressure for attachments		bar		160-180	160-180	160-180
	8.3	Oil volume for attachments		l/min		70	70	70
	8.4	Sound level at the driver's ear according to EN 12 053		dB(A)		68	68	68

All data are based on table configuration. Other configurations may give other values.

Truck performance and dimensions are nominal and subject to tolerances.

Products and specifications are subject to change without notice.

Mast dimensions and rated capacities


Model			V								FV/FW					FSV/FSW									
8FBMT40, 8FBMT45	Lift height	h_{23}	3050	3350	3750	4050	4550	5050	5550	—	3050	3350	3750	4050	—	4200	—	4450	4750	5050	5550	6050	6550		
	Lift	h_3	3000	3300	3700	4000	4500	5000	5500	—	3000	3300	3700	4000	—	4150	—	4400	4700	5000	5500	6000	6500		
	Height, mast lowered	h_1	2360	2500	2750	2880	3130	3380	3630	—	2360	2500	2750	2880	—	2200	—	2360	2440	2500	2750	2880	3130		
	Height, mast extended ¹⁾	h_4	3856	4156	4560	4856	5356	5856	6356	—	3890	4190	4590	4890	—	5040	—	5290	5590	5890	6390	6890	7390		
	Height, mast extended ²⁾	h_4	4220	4520	4920	5220	5720	6220	6720	—	4220	4520	4920	5220	—	5370	—	5620	5920	6220	6720	7220	7720		
	Free lift, without load backrest	h_2	80	80	80	80	80	80	80	—	1470	1610	1860	1990	—	1310	—	1470	1550	1610	1860	1990	2240		
	Free lift, with load backrest	h_2	80	80	80	80	80	80	80	—	1140	1280	1530	1660	—	1140	—	980	1220	1280	1530	1660	1910		
8FBMT50	Lift height	h_{23}	3060	3360	3760	4060	4560	5060	5560	2860	—	3360	3760	4060	4060	—	4360	—	4760	5060	5560	6060	6560		
	Lift	h_3	3000	3300	3700	4000	4500	5000	5500	2800	—	3300	3700	4000	4000	—	4300	—	4700	5000	5500	6000	6500		
	Height, mast lowered	h_1	2360	2500	2750	2880	3130	3380	3630	2360	—	2630	2880	3130	2200	—	2360	—	2500	2630	2880	3130	3380		
	Height, mast extended ¹⁾	h_4	3956	4156	4560	4856	5356	5856	6356	3690	—	4190	4590	4890	4890	—	5190	—	5590	5890	6390	6890	7390		
	Height, mast extended ²⁾	h_4	4220	4520	4920	5220	5720	6220	6720	4020	—	4520	4920	5220	5220	—	5520	—	5920	6220	6720	7220	7720		
	Free lift, without load backrest	h_2	80	80	80	80	80	80	80	1470	—	1740	1990	2240	1310	—	1470	—	1610	1740	1990	2240	2490		
	Free lift, with load backrest	h_2	80	80	80	80	80	80	80	1160	—	1430	1680	1930	1000	—	1140	—	1280	1410	1660	1910	2160		

1) Without load backrest.

2) With load backrest; Height of standard load backrest is 1200 mm.


Pneumatic shaped cushion tyre			V							FV/FW					FSV/FSW									
8FBMT40	Tilt range, forward	deg	5	5	5	5	5	5	5	—	5	5	5	5	—	5	—	5	5	5	5	5	5	5
	Tilt range, backward	deg	10(6)	10(6)	10(6)	10(6)	6	6	6	—	10(6)	10(6)	10(6)	10(6)	—	6	—	6	6	6	6	6	6	6
	Load capacity at 500 mm LC	kg	4000	4000	4000	4000	4000	4000	3950	—	4000	4000	4000	4000	—	4000	—	4000	4000	4000	3850	3710	3400	3400
8FBMT45	Tilt range, forward	deg	5	5	5	5	5	5	5	—	5	5	5	5	—	5	—	5	5	5	5	5	5	5
	Tilt range, backward	deg	10(6)	10(6)	10(6)	10(6)	6	6	6	—	10(6)	10(6)	10(6)	10(6)	—	6	—	6	6	6	6	6	6	6
	Load capacity at 500 mm LC	kg	4500	4500	4500	4500	4500	4500	4450	—	4500	4500	4500	4500	—	4500	—	4500	4500	4470	4340	4210	3650	3650
8FBMT50	Tilt range, forward	deg	5	5	5	5	5	5	5	5	—	5	5	5	5	—	5	—	5	5	5	5	5	5
	Tilt range, backward	deg	10(6)	10(6)	10(6)	10(6)	6	6	6	10(6)	—	10(6)	10(6)	10(6)	6	—	6	—	6	6	6	6	6	6
	Load capacity at 600 mm LC	Kg	4990	4990	4990	4990	4990	4990	4950	4990	—	4990	4990	4990	4990	—	4990	—	4970	4890	4750	4610	3850	3850

Data in () are for when "Cabin Series" or front windshield is selected.



Standard equipments:

- Toyota SAS (System of Active Stability)
- Toyota AC power system
- Operator presence sensing system (OPS)
- Toyota ORS seat (Operator Restraint System)
- Seat mounted hydraulic minilevers
- Wide visible mast (MFH:3300)
- Long forks [length: 1000 mm (8FBMT40-45), 1200 mm (8FBMT50)]
- Long forkbar [length:1170 mm (8FBMT40-50)]
- 3 way valves
- Wet disc brakes
- Wide brake pedal
- Pneumatic shaped cushion tyres
- Full hydraulic power steering
- Digital Multifunction Display with wheel indicator
- Memory tilt steering column
- Emergency stop button in armrest



TMHE-Toyota Material Handling Europe, version 10.2, 2023-12-20

TOYOTA

MATERIAL HANDLING